



PIN OUT

P1	P2
1	11
3	12
5	10
7	8
9	9
11	7
13	5
15	6
17	4
19	19
2	18
4	13
6	14
8	2
10	3
12	1
14	16
16	15
18	17
20 (no connection)	20

NOTES:

1. ALL COMPONENTS ARE RoHS COMPLIANT.
2. 100% OPEN AND SHORT TEST.
3. CONDUCTOR RESISTANCE: 3 OHMS
4. INSULATION RESISTANCE: 10 MEGOHMS.
5. HI-POT: DC200V/0.01S

⑤	TAG	1PCS	DELTAACO TAG
④	HOOD MOLDED	1PCS	WHITE PVC
③	CONNECTOR	1PCS	MINI DISPLAYPORT 20P MALE GOLD PLATED
②	CONNECTOR	1PCS	DISPLAYPORT 20P MALE GOLD PLATED
①	CABLE	1PCS	[(34AWGx1PAIR)+D+FAM]x5+(34AWGx4C)+ AEB WHITE PVC JACKET OD:5.0+0.2mm
NO.	PARTS NAMF	Q'TY	SPFCIFICATION

APPROVED	CHECKED	DRAWN	CUSTOMER:	
			ITEM NO.	DP-1120
			DRAW NO.	
			UNIT	mm
			SCALE	NONE

DESCRIPTION:

MINI DISPLAYPORT CABLE 20P M
DISPLAYPORT 20P M

